


IMPULSE WRENCHES

YLa SERIES



YLa70A
-70B



YLa80A
-80B



YLa70
-70E



YLa80
-80E



YLa90
-90E



YLa110
-110E

Exterior		Model	Bolt Capacity	Free Speed (Approx.) rpm	Load Air Consumption (Approx.) l/min(ft ³ /min)	Torque Adjustable Range (reference) N·m Air Pressure(dynamic) 0.6MPa (85 lb/in ²)	Overall Length (about) mm(in)	Weight Less Socket or Bit kg(lb)	Spindle Offset (about) mm(in)	Square Drive (Hex.Size of Bit) mm(in)	Noise Level Load 1m dB(A)	Air Inlet Thread (Pipe Thread) Rc	Air Hose Size mm(in)
Body	Spindle												
Pistol	Hex.	YLa70A,70B	M6~8	7000	320 (11.3)	20~28	131 (5.2)	0.79(1.7)	21.5 (0.8)	(6.35) (1/4)	74	1/4	6.4 (1/4)
		YLa80A,80B	M8	7000	350 (12.4)	24~35	138 (5.4)	0.81(1.8)	21.5 (0.8)	(6.35) (1/4)	75	1/4	6.4 (1/4)
	Sq.	YLa70·70E	M6~8	7000	320 (11.3)	24~35	131 (5.2)	0.79(1.7)	21.5 (0.8)	9.5(3/8)	74	1/4	6.4 (1/4)
		YLa80·80E	M8	7000	350 (12.4)	32~50	138 (5.4)	0.81(1.8)	21.5 (0.8)	9.5(3/8)	75	1/4	6.4 (1/4)
		YLa90·90E	M8~10	6500	410 (14.5)	47~65	148 (5.8)	0.95(2.1)	23.0 (0.9)	9.5(3/8)	78	1/4	9.5 (3/8)
		YLa110·110E	M10~12	5500	530 (18.7)	60~95	164 (6.5)	1.33(2.9)	26.5 (1.0)	12.7(1/2)	81	1/4	9.5 (3/8)

■ All models have a hose nipple, 2pcs. hexagon wrenches and a protective cover.
Torque specification is a guideline only. Please select the suitable tool to meet the work condition.